


# DateK Services

Specialist in  
Electronic Engineering

## $\mu$ RTU - 1608



### Key Features:

- Low Cost
- Small size (250mm x 165mm x 60mm)
- DIN rail mountable
- Wide input supply operating range 12v-70v
- Low power consumption
- Powerful 16/32 bit Micro-controller (Motorola 68331)
- 1M byte Static RAM, 1M byte Flash, 0.5 M byte Eprom memory
- Real-time calendar clock
- 3 x Serial Ports ( 2 x RS232/485, 1 x RS232 only )
- 16 x opto-isolator digital inputs (VDR Protected)
- 8 x relay digital outputs (VDR Protected)
- Master execute relays with Live/Isolate switch and stuck contact detection circuitry
- Internally connected Dummy Circuit Breaker
- 8 bit D.I.L. switches (4 off) for configuration
- 2.5mm<sup>2</sup> plant i/o and external supply connections
- Industry standard 9 Way 'D-type' connectors used for serial ports
- Protocols currently supported: MK3, DSP4, RIP
- Protocols (Future): DNP3, IEC870

For further information call us on 0131 665 4677 or email [enquiries@datekservices.com](mailto:enquiries@datekservices.com),  
or visit our website - [www.datekservices.com](http://www.datekservices.com)